

PRODUCT SPECIFICATIONS

KRUGER PACKAGING

XTR

MADE FROM

**100%
RECYCLED
FIBER**

XTR LINERBOARD GRADES (EXTRA HIGH PERFORMANCE)

FSC | ISO 14001 | SFI | ISO 9001 | FDA Compliant | C-TPAT Certified

	UNIT	TEST METHOD	XTR18	XTR20	XTR23	XTR26	XTR28	XTR30	XTR31	XTR33	XTR35
MOISTURE	%	Tappi-412									
> Target			8	8	8	8	8	8	8	8	8
SCT CD	Lbs/in.	Tappi-826									
> Target			10	11,2	13	15	16	17	17,7	19	21
SLIDE ANGLE	Degree	Tappi-814									
> Target			22	22	22	22	22	22	22	22	22
SMOOTHNESS	Microdeviation	Emveco									
> Reject above			200	200	200	200	200	200	200	200	200
POROSITY GURLEY	Sec	Tappi T-460									
> Minimum			20	20	20	20	20	20	20	20	20
UN COBB TOP (2 MIN.)	G/sq. meter	Tappi T-441									
> Reject above			75	75	75	75	75	75	75	75	75

Note: All grades are produced to compression standards with no basis weight limits.

Published date: May 29, 2019