

MADE FROM
100%
RECYCLED
FIBER

PRODUCT SPECIFICATIONS

KRUGER PACKAGING

GreenWhite 161

MILL CODE 08007

PROPERTY	UNITS	REJ MIN	TARGET	REJ MAX
BASIS WEIGHT	lbs/1000 ft ²	32.8	33.0	38.9
BASIS WEIGHT	gsm	160	161	190
CALIPER	pt. (Tappi T 411)	—	7.9	—
CALIPER	μ (Tappi T 411)	—	200	—
MOISTURE	% (Tappi T 412)	4.0	5.5	7.0
BRIGHTNESS, CIE	% (Tappi T 525)	71	74	77
A*	Top (Tappi T 527)	-0.2	0.8	1.8
b*	Top (Tappi T 527)	-2.8	-1.4	0.2
SHEFFIELD TOP (TAPPI T 538)	ml/min. (Tappi T 538)	—	200	—
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	45	70
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	95	105
COBB BOTTOM 30 MIN.	gsm (Tappi T 441)	—	50	70
SCOTT BOND CD	j/m ² (Tappi T 569)	180	210	—
COMPRESSION, STFI, CD	KN/m (Tappi T 826)	—	2.25	—
WAX PICK	N# (Tappi T 459)	13	16	—
WAX Fluff	N# (Tappi T 459)	12	14	—

Optical Properties with a Color Touch (CIE)

Neutral Paper
SFI Certified
FSC Certifiable

Published date - April 2, 2016

Roll Finishing:

GreenWhite wound top side out
Telescopic/Unequal winding: ±0.5 in.
Cores: 4 in. Inside diam., 0,30 in. thick,
Core Spec.: +1/16 in. to -1/4 in. Length
Roll Width ±0.08 in.
2 Straps: at 1.0 ±1/2 in. from roll edges

MADE FROM
100%
RECYCLED
FIBER

PRODUCT SPECIFICATIONS

KRUGER PACKAGING

GreenWhite 183

MILL CODE 09007

PROPERTY	UNITS	REJ MIN	TARGET	REJ MAX
BASIS WEIGHT	lbs/1000 ft ²	37.3	37.5	—
BASIS WEIGHT	gsm	182	183	—
CALIPER	pt. (Tappi T 411)	—	9.3	—
CALIPER	μ (Tappi T 411)	—	235	—
MOISTURE	% (Tappi T 412)	4.0	5.5	7.0
BRIGHTNESS, CIE	% (Tappi T 525)	71	74	77
A*	Top (Tappi T 527)	-0.2	0.8	1.8
b*	Top (Tappi T 527)	-2.8	-1.4	0.2
SHEFFIELD TOP (TAPPI T 538)	ml/min. (Tappi T 538)	—	210	—
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	45	70
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	95	105
COBB BOTTOM 30 MIN.	gsm (Tappi T 441)	—	50	70
SCOTT BOND CD	j/m ² (Tappi T 569)	180	210	—
COMPRESSION, STFI, CD	KN/m (Tappi T 826)	2.55	2.70	—
WAX PICK	N# (Tappi T 459)	13	16	—
WAX Fluff	N# (Tappi T 459)	12	14	—

Optical Properties with a Color Touch (CIE)

Neutral Paper
SFI Certified
FSC Certifiable

Published date - April 2, 2016

Roll Finishing:

GreenWhite wound top side out
Telescopic/Unequal winding: ±0.5 in.
Cores: 4 in. Inside diam., 0,30 in. thick,
Core Spec.: +1/16 in. to -1/4 in. Length
Roll Width ±0.08 in.
2 Straps: at 1.0 ±1/2 in. from roll edges

MADE FROM
100%
RECYCLED
FIBER

PRODUCT SPECIFICATIONS

KRUGER PACKAGING

GreenWhite 205

MILL CODE 10007

PROPERTY	UNITS	REJ MIN	TARGET	REJ MAX
BASIS WEIGHT	lbs/1000 ft ²	41.8	42.0	45.1
BASIS WEIGHT	gsm	204	205	220
CALIPER	pt. (Tappi T 411)	—	10.0	—
CALIPER	μ (Tappi T 411)	—	253	—
MOISTURE	% (Tappi T 412)	4.0	6.2	8.0
BRIGHTNESS, CIE	% (Tappi T 525)	71	74	77
A*	Top (Tappi T 527)	-0.2	0.8	1.8
b*	Top (Tappi T 527)	-2.8	-1.4	0.2
SHEFFIELD TOP (TAPPI T 538)	ml/min. (Tappi T 538)	—	220	—
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	45	70
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	95	105
COBB BOTTOM 30 MIN.	gsm (Tappi T 441)	—	50	70
SCOTT BOND CD	j/m ² (Tappi T 569)	180	210	—
COMPRESSION, STFI, CD	KN/m (Tappi T 826)	2.80	3.00	—
WAX PICK	N# (Tappi T 459)	13	16	—
WAX Fluff	N# (Tappi T 459)	12	14	—

Optical Properties with a Color Touch (CIE)

Neutral Paper
SFI Certified
FSC Certifiable

Published date - April 2, 2016

Roll Finishing:

GreenWhite wound top side out
Telescopic/Unequal winding: ±0.5 in.
Cores: 4 in. Inside diam., 0,30 in. thick,
Core Spec.: +1/16 in. to -1/4 in. Length
Roll Width ±0.08 in.
2 Straps: at 1.0 ±1/2 in. from roll edges

MADE FROM
100%
RECYCLED
FIBER

PRODUCT SPECIFICATIONS

KRUGER PACKAGING

GreenWhite 270

MILL CODE 12707

PROPERTY	UNITS	REJ MIN	TARGET	REJ MAX
BASIS WEIGHT	lbs/1000 ft ²	54.9	55.3	—
BASIS WEIGHT	gsm	268	270	—
CALIPER	pt. (Tappi T 411)	—	13.0	—
CALIPER	μ (Tappi T 411)	—	330	—
MOISTURE	% (Tappi T 412)	4.5	7.0	8.5
BRIGHTNESS, CIE	% (Tappi T 525)	71	74	77
A*	Top (Tappi T 527)	-0.2	0.8	1.8
b*	Top (Tappi T 527)	-2.8	-1.4	0.2
SHEFFIELD TOP (TAPPI T 538)	ml/min. (Tappi T 538)	—	250	—
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	45	70
COBB TOP 2 MIN.	gsm (Tappi T 441)	—	95	105
COBB BOTTOM 30 MIN.	gsm (Tappi T 441)	—	50	70
SCOTT BOND CD	j/m ² (Tappi T 569)	—	210	—
COMPRESSION, STFI, CD	KN/m (Tappi T 826)	3.95	4.50	—
WAX PICK	N# (Tappi T 459)	13	16	—
WAX Fluff	N# (Tappi T 459)	12	14	—

Optical Properties with a Color Touch (CIE)

Neutral Paper
SFI Certified
FSC Certifiable

Published date - April 2, 2016

Roll Finishing:

GreenWhite wound top side out
Telescopic/Unequal winding: ±0.5 in.
Cores: 4 in. Inside diam., 0,30 in. thick,
Core Spec.: +1/16 in. to -1/4 in. Length
Roll Width ±0.08 in.
2 Straps: at 1.0 ±1/2 in. from roll edges