

## PRODUCT SPECIFICATIONS

# KRUGER PACKAGING

**XTR**

MADE FROM

**100%  
RECYCLED  
FIBER**

## XTR LINERBOARD GRADES (EXTRA HIGH PERFORMANCE)

	UNIT	TEST METHOD	XTR18	XTR20	XTR23	XTR26	XTR28	XTR30	XTR31	XTR33	XTR35
<b>MOISTURE</b>	%	Tappi-412									
> Target			8	8	8	8	8	8	8	8	8
<b>SCT CD</b>	Lbs/in.	Tappi-826									
> Target			10	11,2	13	15	16	17	17,7	19	21
<b>SLIDE ANGLE</b>	Degree	Tappi-814									
> Target			22	22	22	22	22	22	22	22	22
<b>SMOOTHNESS</b>	Microdeviation	Emveco									
> Reject above			200	200	200	200	200	200	200	200	200
<b>POROSITY GURLEY</b>	Sec	Tappi T-460									
> Minimum			20	20	20	20	20	20	20	20	20
<b>UN COBB TOP (2 MIN.)</b>	G/sq. meter	Tappi T-441									
> Reject above			75	75	75	75	75	75	75	75	75

**Note: All grades are produced to compression standards with no basis weight limits.**

Published date: August 24, 2018