

## PRODUCT SPECIFICATIONS

# KRUGER PACKAGING

**XTR**

MADE FROM

**100%**  
RECYCLED  
FIBER

## XTR LINERBOARD GRADES (EXTRA HIGH PERFORMANCE)

FSC | ISO 14001 | SFI | ISO 9001 | FDA Compliant | C-TPAT Certified

	UNIT	TEST METHOD	XTR18	XTR20	XTR23	XTR26	XTR28	XTR30	XTR31	XTR33	XTR35	XTR42
<b>MOISTURE</b>	%	Tappi-412										
› Target			8	8	8	8	8	8	8	8	8	8
<b>SCT CD</b>	Lbs/in.	Tappi-826										
› Target			10	11,2	13	15	16	17	17,7	19	21	-
<b>RCT CD</b>	Lbf/6 in.	Tappi-822										
› Target			-	-	-	-	-	-	-	-	-	90
<b>SLIDE ANGLE</b>	Degree	Tappi-814										
› Target			22	22	22	22	22	22	22	22	22	22
<b>SMOOTHNESS</b>	Microdevia- tion	Emveco										
› Reject above			200	200	200	200	200	200	200	200	200	200
<b>POROSITY GURLEY</b>	Sec	Tappi T-460										
› Target			20	20	20	20	20	20	20	20	20	20
<b>COBB TOP (2 min. )</b>	G/sq.meter	Tappi T-441										
› Reject above			75	75	75	75	75	75	75	75	75	75

Note: All grades are produced to compression standards with no basis weight limits.

Published date: April 3, 2023