

PRODUCT SPECIFICATIONS

KRUGER PACKAGING

XTR 

MADE FROM
100%
RECYCLED
FIBER

XTR LINERBOARD GRADES (EXTRA HIGH PERFORMANCE)

FSC | ISO 14001 | SFI | ISO 9001 | FDA Compliant | C-TPAT Certified

| | UNIT | TEST METHOD | XTR18 | XTR20 | XTR23 | XTR26 | XTR28 | XTR30 | XTR31 | XTR33 | XTR35 | XTR42 | XTR46 |
|--------------------------|-----------------|-------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| MOISTURE | % | Tappi-412 | | | | | | | | | | | |
| › Target | | | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 | 8 |
| SCT CD | Lbs/in. | Tappi-826 | | | | | | | | | | | |
| › Target | | | 10 | 11,2 | 13 | 15 | 16 | 17 | 17,7 | 19 | 21 | - | - |
| RCT CD | Lbf/6 in. | Tappi-822 | | | | | | | | | | | |
| › Target | | | - | - | - | - | - | - | - | - | - | 90 | 100 |
| SLIDE ANGLE | Degree | Tappi-814 | | | | | | | | | | | |
| › Target | | | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 22 |
| SMOOTHNESS | Micro-deviation | Emveco | | | | | | | | | | | |
| › Reject above | | | 200 | 200 | 200 | 200 | 200 | 200 | 200 | 200 | 200 | 200 | 200 |
| POROSITY GURLEY | Sec | Tappi T-460 | | | | | | | | | | | |
| › Target | | | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| COBB TOP (2 min.) | G/sq. meter | Tappi T-441 | | | | | | | | | | | |
| › Reject above | | | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 | 75 |

Note: All grades are produced to compression standards with no basis weight limits.

Published date: March 21, 2024